

## AquaKwik LF6x –Windshield washer fluid

NuGeneration Technologies' Windshield Washer Fluid, AquaKwik LF6x is a neutral pH aqueous liquid concentrated cleaner. As Supplied the concentrate is a Zero Fahrenheit freeze grade. Non-streaking and non-spotting formula leaves windshields free of road film, dirt, grime, dust, water-spots and bugs. Highly effective products removes even the toughest "bug-splat" marks. 20°F windshield washer fluid is an excellent "De-Icer" and won't freeze in your reservoir at temperatures as low as 20 degrees Fahrenheit. Concentrated windshield washer fluid is an economical alternative to buying ready to use fluids.



### Typical Usage Parameters & Mixtures:

	6x Concentrate	3:1 dilution	6:1 dilution	12:1 dilution
Freezing Temperature	0°F	10°F	20°F	30°F
Dilution Ratio (Water:LF6x)	0:1 Use Full strength	3:1	6:1	12:1
Dilute with water to %	100%	25%	14%	7%


### Physical Properties:

	6x Concentrate	3:1 dilution	6:1 dilution	12:1 dilution
pH, Concentrate	9.0	8.7	8.5	8.3
Bulk Density, #/gal	8.0	8.26	8.30	8.34
Flash Point	> 114°F	> 140°F	> 175°F	None to boil
VOC (Concentrate)	<160 g / liter	<52 g / liter	<26 g / liter	<13 g / liter

### Force Flow Mixing Units for Automated Dilutions of LF6X:

The Force-Flo Mixer blends and dispenses LF6X with water automatically for uniform solutions at any proportion. The mixer inserts into any 55 gallon drum (3" standard bung required). Water line pressure (25 lb minimum operating pressure) is all that is necessary to operate the unit. The mixer can dispense in approximately 1/10th the time of manual methods and can save up to 25% of coolant per month. The mixer is simple to operate, is made of non-corrosive metal and has no moving parts.

Warranty: FREE 10-year repair or replacement for any unit that fails. Force Flow Coolant Mixers are the #1 Industry Standard Mixing unit. We have sold these units for more than 15 years and have a >99.5% Satisfaction rate. Some Force Flo units have been in service for over 20 years.



Force Flow Unit: BP88-CX-2164 ¾" STD Pipe thread fittings or BP88-CX-2164G with Garden Hose fittings is recommended for LF6X. This unit can handle all three dilution ratios 10F, 20F and 30F.

**Availability:** 55-gallon containers or 2,000 to 4,500-gallon bulk tank shipments.

**Shipment:** Freight Classification Flammable Liquid, Toxic N.O.S. (Methanol Mixture) UN1992, PG II.

**Storage:** Keep out of direct sunlight. Keep from freezing. Store from 40-100°F.

<sup>(1)</sup>**Disposal:** Dispose of in accordance with local, state, & federal regulations. For assistance with disposal contact NuGeneration Technologies at 888-99-NuGen or email:

[info@nugentec.com](mailto:info@nugentec.com)

