

### STRIPPER X 4: Aqueous & Non-Corrosive Stripper / De-Bonder. Removes Paints, Synthetic Finishes, Resins, Inks, Gums And Oils.

#### Description:

Stripper X 4 is a mildly alkaline (pH 10) aqueous stripper / de-bonder. Stripper X 4 is highly effective, cost efficient, biodegradable, and safe to use. Stripper X 4 is a liquid alkaline cleaning product designed to remove paints, synthetic finishes, vinyl, baked acrylics, epoxies, polyurethanes, alkyds, polyesters, melamines, resins, particles and metal salts as well as greases and oils, including fingerprints. Stripper X 4 is designed to remove finishes from steel and other metal parts, however it will cause attack on aluminum and zinc. Its effectiveness and long tank life make it one of the most economical strippers on the market today.

- Non-nitrated – prevents formations of nitrosamines
- Degreases
- Rinses Freely
- NON-CORROSIVE
- Bio-resistant – aids in tank life and pH control
- Removes Salts
- Works Quickly
- LOW VOC
- 

#### Typical Usage Parameters:

	Stripper X 4
Description	Ferrous & non-ferrous Spray & Immersion
Concentration Range	15 to 50%
Operating Temperatures	180 up to 200°F (do not boil)
Time (Min)	As required 3-30 minutes
Ferrous Metals	YES
Aluminum, Zinc, Galvanized Steel	NO

#### Physical Properties:

	Stripper X 4
pH, Concentrate	10
pH, @ 25% bv	10
Bulk Density, #/gal	7.6
VOC	500 g/L
Flash Point	>190°F
Chelates	NO
Solubility In Water	Complete
Biodegradable Surfactants	YES
Phosphate Free	YES

## **STRIPPER X 4: Liquid Alkaline Aqueous Stripper / De-Bonder. Removes Paints, Synthetic Finishes, Resins, Inks, Gums And Oils.**

### **Application:**

Stripper X 4 is applied by immersion. Stripper X 4 should be run at 25 to 50% with water at 150-200<sup>(1)</sup>°F (66 to 93°C). Do not boil. Exact concentrations will depend on material to be removed and processing times required. Stripping times will range from 3 minutes to 30 minutes or longer. Consult your NuGeneration Technologies Technical Sales Representative for assistance.

<sup>(1)</sup> Care should be used at temperatures above 180°F, as the flash point on this material is ~190°F.

### **NOTES:**

- Always read MSDS (Material Safety Data Sheet) before using
- Be sure to stir while making solutions to create a homogenous mixture
- This product is considered non-corrosive per DOT and IATA
- May cause attack on rubber, aluminum and zinc.

**Safety Information:** Stripper X 4 is a moderately alkaline material containing amines. Do not mix with nitrates to prevent formation of hazardous nitrous-amines. Direct contact may cause irritation or even burns of eyes and skin. It is harmful if swallowed or inhaled. Avoid contact with eyes, skin and clothing. Wear rubber gloves, safety glasses or face shield, and suitable protective clothing when handling. Wash thoroughly after handling. Avoid breathing mist. Use only with adequate ventilation. Do not take internally. **KEEP OUT OF REACH OF CHILDREN.**

**First Aid in Case of Contact:** Immediately flush eyes and skin with plenty of water for at least 15 minutes. Get medical attention. For skin, remove contaminated clothing and shoes. Wash them before reuse. If swallowed, wash out mouth thoroughly with water. Give several glasses of milk to drink. Do not induce vomiting. Consult a physician.

**HMS Rating:** 1,1,0,C

**Bath control:** Use NuGenTec Free alkalinity titration procedure for Stripper X 4.

**Availability:** Available in 5, 55 and 300-gallon containers. Bulk tank shipments also available.

**Shipment:** Freight classification: "Cleaning Compound, NOBIN, Non-regulated material."

**Storage:** Keep from freezing. Store between 40-100°F.

**Disposal:** Dispose of in accordance with local, state, and federal regulations. For assistance with disposal contact NuGeneration Technologies at 888-99-NuGen or email: [info@nugentec.com](mailto:info@nugentec.com).