

Absorbent Material

Technical Data Sheet

Premium Absorbent

Granular Absorbents

Description:

NuGenTec's General Purpose Absorbent, is a dust free granular material which will absorb both aggressive and non-aggressive fluids including oil, acid, paint, ink and water. Use NuGenTec's General Purpose Absorbent to reduce hazards and slipping accidents by keeping floors dry. For information on this product and our other absorbent products please contact our technical department 1-888-996-8436 www.nugentec.com

Characteristics:

Compliance: CA Prop 65

Absorption Capacity: Approx. 3 to 5 gallons. Varies depending on liquid type.

Application: Absorbs spills from oil and water

Color: Off-White

Container Type: Bag

Material: Clay.

Note: Contains less than 0.1% free crystalline silicate when tested IAW NIOSH Method 7500


Type: Granular Absorbent

Product weight: 44 lbs net weight minimum



Product Benefits

- Use for all non-aggressive fluids
- Won't turn into mud
- Lower airborne contamination
- More scoops per pound



Physical Properties	
Density	19.477 lbs/gal
Ignition Temperature	>370C (>698F)
pH, Concentrate	N/A
pH, @5%	N/A
Flash Point	500C (932F)
Boiling Point	2230C (4046F)
Vapor Pressure	N/A
Soluble in water	Absorbs
Biodegradable	Yes
Corrosive	No

Availability: 44 lb bags net weight MINIMUM

Shipment: DOT – NON Regulated Material

Storage: Keep away from liquids until use

Disposal: Dispose of in accordance with local, state, and federal regulations. For assistance with disposal contact NuGeneration Technologies at 888-99-NuGen or email: salesteam@nugentec.com.

This product is classified and labeled according to the Globally Harmonized System (GHS).

**1155 Park Avenue
Emeryville, CA 94608**

(888) 99-NuGen
(888) 996-8436
Fax (707) 891-3012

www.NuGenTec.com
info@NuGenTec.com

EMERGENCY OVERVIEW:

This product may cause inhalation irritation.

SAFETY:

Please make sure you have read and understand the product label and MSDS before using this product. Avoid breathing vapors, spray or mists. Use only with adequate ventilation. Wash thoroughly after handling. Observe label precautions.